

API Developer Notes

Adding Agency Service Fees Using TASF

6 October 2011

Version 1.1

THE INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND PROPRIETARY TO TRAVELPORT

Copyright

Copyright © 2011 Travelport and/or its subsidiaries. All rights reserved.

Travelport provides this document for information purposes only and does not promise that the information contained in this document is accurate, current or complete. This document is subject to change without notice.. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or any means electronic or mechanical, including photocopying and recording for any purpose other than the licensee's personal use without the prior written permission of Travelport and/or its subsidiaries.

Trademarks

Travelport and/or its subsidiaries may have registered or unregistered patents or pending patent applications, trademarks copyright, or other intellectual property rights in respect of the subject matter of this document. The furnishing of this document does not confer any right or license to or in respect of these patents, trademarks, copyright, or other intellectual property rights.

All other companies and product names are trademarks or registered trademarks of their respective holders.

Contents

Overview	1
Starting a Host Session	1
Retrieving the PNR	1
Issuing the Travel Agency Service Fee (TASF)	2
TASF Request	2
TASF Response.....	3
Ending the Host Session	3

Overview

Agency fees can be added to a PNR using the Travel Agency Service Fee (TASF) facility provided by the Airline Reporting Corporation (ARC). TASFs are created using the `TravelAgentServiceFees_#` transaction.

The steps to add a TASF to an existing PNR are:

1. Start a host session.
2. Retrieve the PNR.
3. Issues the TASF (if successful, end transacts the PNR).
4. End the host session.

Starting a Host Session


Start a host session by calling the `BeginSession` method of the XML Select Web Services (XWS). Your Host Access Profile (HAP) is required to access XWS.

The `BeginSession` method returns a session token, which is then used for the subsequent session requests (see the **API Developer Notes: *Galileo Web Services Host Sessions*** for details).

Retrieving the PNR

Use `PNRBFManagement_#` request to retrieve the desired PNR. You must include the record locator in the `PNRBFManagement` request.

```
<PNRBFManagement_#>
  <PNRBFRetrieveMods>
    <PNRAddr>
      <FileAddr/>
      <CodeCheck/>
      <RecLoc>JGJ25W</RecLoc>
    </PNRAddr>
  </PNRBFRetrieveMods>
  <FareRedisplayMods>
    <DisplayAction>
      <Action>D</Action>
    </DisplayAction>
  </FareRedisplayMods>
</PNRBFManagement_#>
```



Issuing the Travel Agency Service Fee (TASF)

After you retrieve the PNR, use the TravelAgentServiceFees_# transaction request to create the TASF. You must enter:

- The passenger name.
- The amount of the service fee.
- The currency in which the service fee will be charged.
- Credit card data for the passenger.

The PNR provides basic information, but the service fee information, <ServiceFeeInfo>, comes from your agency policies.

TASF Request

```
<TravelAgentServiceFees_#>
  <ServiceFeeMods>
    <ServiceFeeInfo>
      <Name>JOHN.SMITH</Name>
      <Amt>25.00</Amt>
      <CurrencyCode>USD</CurrencyCode>
      <RelatedTktNum></RelatedTktNum>
    </ServiceFeeInfo>
    <CreditCardFOP>
      <ExpDt>0307</ExpDt>
      <Vnd>AX</Vnd>
      <Acct>3000000000000000</Acct>
      <AdditionalInfoAry>
        <AdditionalInfo>
          <ID>1</ID>
          <Dt>4098</Dt>
        </AdditionalInfo>
      </AdditionalInfoAry>
    </CreditCardFOP>
  </ServiceFeeMods>
</TravelAgentServiceFees_#>
```


Annotations:

- FirstName.LastName points to <Name>JOHN.SMITH</Name>
- Service fee amount points to <Amt>25.00</Amt>
- 1 = Credit card approval code points to <ID>1</ID>
- Credit card approval code value points to <Dt>4098</Dt>

TASF Response

A successful TASF response end transacts the PNR.

```
<TravelAgentServiceFees_# xmlns="">
  <ServiceFee>
    <RecordLocator>
      <RecLoc>JGJ25W</RecLoc>
    </RecordLocator>
    <TicketNumInfo>
      <PrimeTktNum>8909900292971</PrimeTktNum>
      <ConjunctiveTktNum/>
      <NumTks/>
    </TicketNumInfo>
  </ServiceFee>
</TravelAgentServiceFees_#>
```



Document number
for service fee

Ending the Host Session

End the host session by calling the *EndSession* method of GWS.